

切削参数参考表
Recommended Milling Conditions

| 加工材料 Work Material | | 石墨 Graphite | | | | 铝合金压铸件 Aluminium Alloy Die Casting | | | |
|-----------------------|-------------------------|---|--------------|---------------------|-------|---------------------------------------|--------------|---------------------|-------|
| (R)球头半径 Radius | 颈长 Under Neck Length | 主轴转速 Spindle Speed | 进给速度 Feed | 切深量 Depth of Cut | | 主轴转速 Spindle Speed | 进给速度 Feed | 切深量 Depth of Cut | |
| | | min ⁻¹ | mm/min | Δp mm | Δe mm | min ⁻¹ | mm/min | Δp mm | Δe mm |
| 0.2 | 1 | 40,000 | 1,500 | 0.08 | 0.1 | 20,000 | 800 | 0.05 | 0.08 |
| | 2 | 40,000 | 1,200 | 0.05 | 0.1 | 20,000 | 600 | 0.02 | 0.05 |
| | 4 | 30,000 | 1,000 | 0.05 | 0.1 | 20,000 | 200 | 0.01 | 0.02 |
| | 6 | 30,000 | 800 | 0.03 | 0.1 | 20,000 | 120 | 0.01 | 0.01 |
| 0.3 | 3 | 30,000 | 1,500 | 0.1 | 0.2 | 20,000 | 1,000 | 0.05 | 0.1 |
| | 6 | 30,000 | 1,200 | 0.08 | 0.2 | 20,000 | 600 | 0.03 | 0.05 |
| | 9 | 25,000 | 1,000 | 0.07 | 0.15 | 18,000 | 400 | 0.01 | 0.02 |
| | 12 | 20,000 | 800 | 0.05 | 0.1 | 15,000 | 200 | 0.01 | 0.01 |
| 0.5 | 4 | 30,000 | 2,500 | 0.2 | 0.3 | 20,000 | 2,000 | 0.2 | 0.3 |
| | 6 | 25,000 | 2,000 | 0.15 | 0.3 | 20,000 | 1,500 | 0.1 | 0.3 |
| | 10 | 20,000 | 1,800 | 0.1 | 0.3 | 15,000 | 800 | 0.05 | 0.1 |
| | 16 | 18,000 | 1,200 | 0.08 | 0.2 | 12,000 | 500 | 0.03 | 0.08 |
| | 20 | 15,000 | 1,000 | 0.07 | 0.2 | 8,000 | 300 | 0.02 | 0.05 |
| 1 | 6 | 20,000 | 3,000 | 0.5 | 0.6 | 20,000 | 2,000 | 0.3 | 0.6 |
| | 10 | 20,000 | 2,500 | 0.3 | 0.6 | 20,000 | 1,500 | 0.3 | 0.6 |
| | 16 | 18,000 | 2,000 | 0.2 | 0.6 | 15,000 | 1,200 | 0.2 | 0.5 |
| | 20 | 15,000 | 1,500 | 0.2 | 0.5 | 10,000 | 1,000 | 0.1 | 0.2 |
| | 30 | 12,000 | 1,000 | 0.2 | 0.5 | 8,000 | 500 | 0.05 | 0.1 |
| 1.5 | 20 | 20,000 | 2,500 | 0.5 | 1 | 15,000 | 1,500 | 0.5 | 1 |
| | 40 | 12,000 | 1,400 | 0.3 | 0.7 | 7,000 | 600 | 0.1 | 0.3 |
| 2 | 15 | 20,000 | 3,000 | 0.5 | 1.5 | 16,000 | 2,000 | 0.5 | 1.5 |
| | 30 | 15,000 | 2,500 | 0.5 | 1.5 | 12,000 | 1,500 | 0.5 | 1.2 |
| | 40 | 12,000 | 2,000 | 0.3 | 1 | 8,000 | 1,000 | 0.2 | 0.7 |
| 3 | 30 | 16,000 | 3,000 | 0.6 | 2 | 12,000 | 2,000 | 0.6 | 2 |
| | 60 | 8,000 | 2,000 | 0.4 | 2 | 7,000 | 1,000 | 0.3 | 1 |
| 备 注 Notes | | ※1 加工石墨时, 请使用石墨专用的加工机床。 此外, 进行加工或者操作时为了防止粉尘飞扬或者被吸入身体, 请使用吸尘器和防尘口罩。 ※2 石墨加工建议采用干式切削。 ※3 如果刀具发生崩刃, 或者需要高精度加工时, 请降低进给速度。 ※4 发生振刀时, 请以相同的比率降低主轴转速和进给速度。 此外, 主轴转速过低时, 也以相同的比率降低。 ※1 Graphite should be machined by the machining center designed for graphite machining. When handling with graphite material, dust collector and respirator are recommended to protect against graphite dust. ※2 Air blow cooling is recommended for the machining of graphite. ※3 Reduce the feed for high accurate machining and to avoid breakage of work piece. ※4 Adjust both spindle speed and feed at the same rate when chattering. | | | | | | | |

0 石墨
Graphite
 石墨加工
Graphite Milling